DOLL

SAFETY DATA SHEET

1. Identification

Product identifier KOOL ALL

METALWORKING FLUID

Other means of identification

SDS number Not applicable

Recommended use METALWORKING FLUID

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name DOALL SAWING PRODUCTS

A DOALL COMPANY 2375 Toughy Avenue Elk Grove Village, IL 60007

Telephone (General

Information)

Emergency telephone

number

Emergency telephone number (outside USA)

888-362-5572, Ext 65047

1-800-424-9300 (CHEMTREC)

1-703-527-3887 (CHEMTREC)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin irritation Category 2

Serious eye irritation Category 2
Sensitization, skin Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Precautionary statement

Prevention Avoid breathing mist or vapor. Wash thoroughly after handling. Contaminated work clothing must

not be allowed out of the workplace. Wear eye protection/face protection. Wear protective gloves.

ResponseIf on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Take off

contaminated clothing and wash before reuse.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Material name: KOOL ALL SDS US

The classified hazards shown on this SDS are associated with the product concentrate. These hazards are not expected under recommended use conditions and dilution.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM		64742-52-5	10 - 30
DIETHYLENE GLYCOL MONOBUTYL ETHER		112-34-5	1 - 5
HEXAHYDRO-1,3,5-TRIS (2-HYDROXYETHYL)-S- TRIAZINE		4719-04-4	1 - 5
TRIETHANOLAMINE		102-71-6	1 - 5
MONOETHANOLAMINE		141-43-5	0.5 - 1.5
Other components below reportable	levels		60 - 100

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a POISON CENTER or doctor/physician if you feel unwell. Under normal

conditions of intended use, this material is not expected to be an inhalation hazard.

Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing Skin contact

and shoes. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated

clothing before reuse.

Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical Eye contact

attention if irritation develops and persists.

Rinse mouth. Drink 1 or 2 glasses of water. Do not induce vomiting. If vomiting occurs, keep head Ingestion

low so that stomach content doesn't get into the lungs. Call a POISON CENTER or

doctor/physician if you feel unwell.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

redness, swelling, and blurred vision. Skin irritation. May cause an allergic skin reaction.

Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing,

General information If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in

attendance.

5. Fire-fighting measures

Suitable extinguishing media

Foam. Dry chemical powder. Carbon dioxide (CO2). Use extinguishing measures that are

appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Wear suitable protective equipment.

Fire fighting

equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.

Specific methods

General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: KOOL ALL SDS US

Methods and materials for containment and cleaning up

Local authorities should be advised if significant spillages cannot be contained. This product is miscible in water. Clean up in accordance with all applicable regulations.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not get in eyes, on skin, or on clothing. Avoid breathing mist or vapor. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Do not allow material to freeze. Store away from incompatible materials (see Section 10 of the SDS). If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA

0.0. 00.0.				
	Туре	Value		
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM (CAS 64742-52-5)	PEL	5 mg/m3		
US. OSHA Table Z-1 Limits for Air C	Contaminants (29 CFR 1910.1000)			
	Туре	Value		
MONOETHANOLAMINE (CAS 141-43-5)	PEL	6 mg/m3		
		3 ppm		
U.S NIOSH				
	Туре	Value		
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM (CAS 64742-52-5)	STEL	10 mg/m3		
,	TWA	5 mg/m3		
US. NIOSH: Pocket Guide to Chemi	cal Hazards	3		
	Туре	Value		
MONOETHANOLAMINE (CAS 141-43-5)	STEL	15 mg/m3		
		6 ppm		
	TWA	8 mg/m3		
		3 ppm		
ACGIH				
	Туре	Value		
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM (CAS 64742-52-5)	TWA	5 mg/m3		
US. ACGIH Threshold Limit Values			_	
	Туре	Value	Form	
MONOETHANOLAMINE (CAS 141-43-5)	STEL	6 ppm		
atarial name: KOOL ALL				CDC LIC

Material name: KOOL ALL SDS US

US. ACGIH Threshold Limit Values

	Туре	Value	Form
TRIETHANOLAMINE (CAS 102-71-6)	TWA	5 mg/m3	
MONOETHANOLAMINE (CAS 141-43-5)	TWA	3 ppm	
DIETHYLENE GLYCOL MONOBUTYL ETHER (CAS 112-34-5)	TWA	10 ppm	Inhalable fraction and vapor.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Do not get in eyes. Eye wash fountain is Eye/face protection

recommended.

Skin protection

Use protective gloves made of: Nitrile. **Hand protection** Other Wear suitable protective clothing.

In case of insufficient ventilation, wear suitable respiratory equipment. Respiratory protection

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

CLEAR Appearance Physical state Liquid. **Form** Liquid. Color Not available.

Odor **CHEMICAL Odor threshold** Not available.

Ha

< 32 °F (< 0 °C) Melting point/freezing point > 212 °F (> 100 °C) Initial boiling point and boiling

range

Flash point Not Applicable

Evaporation rate Like water when diluted

Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flammability limit - upper

Not available.

(%)

(%)

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available.

Not available. Vapor pressure Not available. Vapor density Relative density Not available.

100 % Water Miscible Solubility(ies)

Partition coefficient

(n-octanol/water)

Not available.

Auto-ignition temperature Not available. **Decomposition temperature** Not available.

Material name: KOOL ALL SDS US Viscosity Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

pH in aqueous solution 9.6 @ 5%

Specific gravity 1.009

VOC ASTM D2369 13 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Heat, flames and sparks. Contact with incompatible materials.

Incompatible materials Acids. Oxidizing agents.

Hazardous decomposition

products

Smoke, fumes, and oxides of carbon

11. Toxicological information

Information on likely routes of exposure

Inhalation Not classified.

Skin contact Causes skin irritation. May cause sensitization by skin contact.

Eye contact Causes eye irritation.

Ingestion Not classified.

Symptoms related to the

physical, chemical and

toxicological characteristics

Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing,

redness, swelling, and blurred vision. Skin irritation. May cause an allergic skin reaction.

Information on toxicological effects

Acute toxicity May cause an allergic skin reaction.

Components Species Test Results

DIETHYLENE GLYCOL MONOBUTYL ETHER (CAS 112-34-5)

Acute
Dermal
Liquid

LD50 Rabbit 2764 mg/kg

Oral

LD50 Guinea pig 2000 mg/kg

 Mouse
 2400 mg/kg

 Rabbit
 2200 mg/kg

Liquid

LD50 Rat 3305 mg/kg

MONOETHANOLAMINE (CAS 141-43-5)

Acute Dermal

LD50 Rabbit 1025 mg/kg

Oral

LD50 Guinea pig 620 mg/kg

 Mouse
 700 mg/kg

 Rat
 10.2 g/kg

Material name: KOOL ALL SDS US

Components Species Test Results

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM (CAS 64742-52-5)

Acute
Dermal
Liquid

LD50 Rabbit > 5000 mg/kg

Inhalation

Mist

LC50 Rat 5.7 mg/l, 4 hours

Oral *Liquid*

LD50 Rat > 5000 mg/kg

TRIETHANOLAMINE (CAS 102-71-6)

Acute
Dermal
Liquid

LD50 Rabbit > 2000 mg/kg

Oral

LD50 Guinea pig 5300 mg/kg

Liquid

LD50 Rat 4190 mg/kg

Skin corrosion/irritation Causes skin irritation.
Serious eye damage/eye Causes eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

TRIETHANOLAMINE (CAS 102-71-6) 3 Not classifiable as to carcinogenicity to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure

Not classified.

Specific target organ

Not classified.

toxicity - repeated

Aspiration hazard

exposure

Not an aspiration hazard.

Chronic effects Not classified.

Further information The classification for health and environmental hazards is derived by a combination of calculation

methods and test data, if available.

12. Ecological information

Ecotoxicity Contains a substance which causes risk of hazardous effects to the environment.

Material name: KOOL ALL SDS US

^{*} Estimates for product may be based on additional component data not shown.

Test Results Components **Species**

DIETHYLENE GLYCOL MONOBUTYL ETHER (CAS 112-34-5)

Aquatic

Acute

Crustacea EC50 Daphnia > 100 mg/l, 48 hours Fish LC50 Bluegill (Lepomis macrochirus) 1300 mg/l, 96 hours

MONOETHANOLAMINE (CAS 141-43-5)

Aquatic

Fish Rainbow trout, donaldson trout LC50 114 - 196 mg/l, 96 hours

(Oncorhynchus mykiss)

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM (CAS 64742-52-5)

Aquatic

Acute

LC50 Fish Fish > 100 mg/l, 96 hours

TRIETHANOLAMINE (CAS 102-71-6)

Aquatic

Crustacea EC50 Water flea (Ceriodaphnia dubia) 565.2 - 658.3 mg/l, 48 hours Fish LC50 Fathead minnow (Pimephales promelas) 10610 - 13010 mg/l, 96 hours

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

DIETHYLENE GLYCOL MONOBUTYL ETHER 1 MONOETHANOLAMINE -1.31**TRIETHANOLAMINE** -1

Mobility in soil This product is miscible in water.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established.

the IBC Code

Annex II of MARPOL 73/78 and

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200

^{*} Estimates for product may be based on additional component data not shown.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

HEXAHYDRO-1,3,5-TRIS (2-HYDROXYETHYL)-S-

TRIAZINE (CAS 4719-04-4)

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories**

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Chemical name CAS number % by wt. DIETHYLENE GLYCOL MONOBUTYL ETHER 112-34-5 1 - 5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug

Not regulated.

Administration (FDA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM (CAS 64742-52-5)

US. Massachusetts RTK - Substance List

MONOETHANOLAMINE (CAS 141-43-5)

TRIETHANOLAMINE (CAS 102-71-6)

US. New Jersey Worker and Community Right-to-Know Act

MONOETHANOLAMINE (CAS 141-43-5) TRIETHANOLAMINE (CAS 102-71-6)

US. Pennsylvania Worker and Community Right-to-Know Law

MONOETHANOLAMINE (CAS 141-43-5) TRIETHANOLAMINE (CAS 102-71-6)

US. Rhode Island RTK

Not regulated.

California South Coast Air Quality Management District (SCAQMD) Rule 1144 (VOC Emissions)

This product is subject to SCAQMD Rule 1144; it is compliant and may be sold and used in the SCAQMD. The VOC content of the product is 73 g/L, measured by ASTM Method E-1868-10. This product has a specified use dilution VOC limit of 75 g/L, the maximum dilution concentration is 100 % to maintain compliance.

1.0 % One-Time Export Notification only.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

International Inventories

Country(s) or region Inventory name On inventory or exempt (yes/no)* Australia Australian Inventory of Chemical Substances (AICS) Nο

Material name: KOOL ALL SDS US

Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Inventory name

 Issue date
 03-11-2015

 Revision date
 08-29-2016

Version # 04

Country(s) or region

Further information Not available.

NFPA ratings Health: 1
Flammability: 0
Instability: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material name: KOOL ALL SDS US

On inventory or exempt (yes/no)*