SAFETY DATA SHEET



1. Identification

Product identifier	RUST PREVENTATIVE
	CORROSION PREVENTIVE
Other means of identification	
SDS number	Not applicable
Recommended use	CORROSION PREVENTIVE
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/	Distributor information
Manufacturer	
Company name	DOALL SAWING PRODUCTS A DOALL COMPANY 2375 Touhy Avenue Elk Grove Village, IL 60007
Telephone (General Information)	888-362-5572, Ext 65047
Emergency telephone number	1-800-424-9300 (CHEMTREC)
Emergency telephone number (outside USA)	1-703-527-3887 (CHEMTREC)

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Serious eye damage/eye irritation	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger
Hazard statement	Flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.
Response	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Gently wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. IF exposed or concerned: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Protect from sunlight. Store away from incompatible materials. Store in accordance with local/regional/national/international regulation.

Hazard(s) not otherwise classified (HNOC) Supplemental information

Disposal

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
C9-C11 ISOALKANES		68551-16-6	60 - 100
PETROLEUM DISTILLATES, HYDROTREATED HEAVY PARAFFINIC		64742-54-7	1 - 5
SODIUM ALKYLARYL SULFONATE		78330-12-8	0.5 - 1.5
Other components below reportable leve	els		5 - 10

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. Under normal conditions of intended use, this material is not expected to be an inhalation hazard.
Skin contact	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth thoroughly. Do not give liquids. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.
Most important symptoms/effects, acute and delayed	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Mild skin irritation. Defatting of the skin.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Wash contaminated clothing before reuse. If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance.
5. Fire-fighting measures	
Suitable extinguishing media	Foam. Dry chemical powder. Carbon dioxide (CO2). Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment	Wear suitable protective equipment

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

General fire hazards

Wear suitable protective equipment.

In case of fire and/or explosion do not breathe fumes. Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

Flammable liquid and vapor.

6. Accidental release measures

0. Accidental release meas	50165
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Local authorities should be advised if significant spillages cannot be contained. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. The product is immiscible with water and will spread on the water surface.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Clean up in accordance with all applicable regulations. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Contact local authorities in case of spillage to drain/aquatic environment. Use appropriate containment to avoid environmental contamination.
7. Handling and storage	
Precautions for safe handling	When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. To maintain product quality, do not store in heat or direct sunlight. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). Keep this material away from food, drink and animal feed. Do not allow material to freeze. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

8. Exposure controls/personal protection

Occupational exposure limits

U.S OSHA			
	Туре	Value	
PETROLEUM DISTILLATES, HYDROTREATED HEAVY PARAFFINIC (CAS 64742-54-7)	PEL	5 mg/m3	
C9-C11 ISÓALKANES (CAS 68551-16-6)	PEL	500 ppm	
U.S NIOSH			
	Туре	Value	
C9-C11 ISOALKANES (CAS 68551-16-6)	TWA	350 mg/m3	

ACGIH		
	Туре	Value
PETROLEUM DISTILLATES, HYDROTREATED HEAVY PARAFFINIC (CAS 64742-54-7)	TWA	5 mg/m3
C9-C11 ISOALKANES (CAS 68551-16-6)	TWA	100 ppm
Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.	
Individual protection measures,	, such as personal protective equipm	ient
Eye/face protection	Wear safety glasses with side shields (or goggles). Avoid contact with eyes. Eye wash fountain is recommended.	
Skin protection		
Hand protection	Use protective gloves made of: Nitrile	9.
Other	Wear suitable protective clothing and	l gloves.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.	
Thermal hazards	Wear appropriate thermal protective	clothing, when necessary.
General hygiene considerations	good personal hygiene measures, su	eke. Do not get in eyes, on skin, on clothing. Always observe uch as washing after handling the material and before eating, wash work clothing and protective equipment to remove

9. Physical and chemical properties

	•
Appearance	CLEAR
Physical state	Liquid.
Form	Liquid.
Color	Not available.
Odor	CHEMICAL
Odor threshold	Not available.
рН	Not Applicable
Melting point/freezing point	< 32 °F (< 0 °C)
Initial boiling point and boiling range	365 °F (185 °C)
Flash point	125 °F (51.7 °C) Cleveland Open Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	Insoluble in Water
Partition coefficient (n-octanol/water)	Not available.

Auto-ignition temperature	Not available.	
Decomposition temperature	Not available.	
Viscosity	Not available.	
Other information		
Specific gravity	0.79	
VOC ASTM D2369	85 %	

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Avoid contact with oxidizers or reducing agents.
Hazardous decomposition products	Smoke, fumes, and oxides of carbon

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.
Skin contact	May be irritating to the skin.
Eye contact	Causes serious eye irritation. Direct contact with eyes may cause temporary irritation.
Ingestion	May be fatal if swallowed and enters airways. Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity

May be fatal if swallowed and enters airways. Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

C9-C11 ISOALKANES (CAS 68551-16-6) Acute Dermal LD50 Rabbit LD50 Rabbit LC50 Rat LC50 Rat 12.4 mg/l, 4 hours Oral LD50 Rat 0ral LD50 Rat 34600 mg/kg Chronic Inhalation NOEL Rat Sector Acute Dermal LD50 Rat Sector Inhalation NOEL Rat > 922 ppm, 6 hours PETROLEUM DISTILLATES, HYDROTREATED HEAVY PARAFFINIC (CAS 64742-54-7) Acute Dermal LD50 Rabbit LD50 Rabbit S000 mg/kg Inhalation LC50 Rat C50 Rat C50 Rat C50 Rat C50 Rat	Components	Species	Test Results
Dermal LD50Rabit5400 mg/kgInhalation LD50Rat12.4 mg/k 1 AuousOral LD50Rat34600 mg/kgChronic Inhalation NOELRat922 pgm, 6 hoursInhalation LD50Rat922 pgm, 6 hoursPETER-UETERTETERTETERTETERTETERTETERTFormal LD50Solo mg/kgInhalation LD50RabitSolo mg/kgInhalation LD50RabitSolo mg/kgInhalation LD50RabitSolo mg/kgInhalation LD50RabitSolo mg/kg	C9-C11 ISOALKANES (CAS	S 68551-16-6)	
LD50Rabit15400 mg/kgInhalation12.4 mg/kgLD50Raf12.4 mg/kgOralRaf34000 mg/kgLD50Raf34000 mg/kgChronic10.1 mg/kgInhalation922 pgm, 6 hoursNOELRaf922 pgm, 6 hoursPETER-USTILLATES, HYDENTERATED HEAVY PARAFFINIC (CASS 64742-54	Acute		
Inhalation I2.4 mg/l, 4 hours LC50 Rat 12.4 mg/l, 4 hours Oral J1000000000000000000000000000000000000	Dermal		
LC50Rat12.4 mg/l, 4 hoursOral LD50Rat34600 mg/kgChronicInhalation NOELPatherNOELRat922 ppm, 6 hoursPETRO-USTILLATES, HYD-XTEATED HEAVY PARAFFINIC (CASS 4747-547-547-547-547-547-547-547-547-547	LD50	Rabbit	15400 mg/kg
Oral Rat 34600 mg/kg LD50 Rat 34600 mg/kg Chronic Inhalation > 922 ppm, 6 hours NOEL Rat > 922 ppm, 6 hours PETROLEUM DISTILLATES, HYDRYTREATED HEAVY PARAFFINIC (CAS 64742-54-7) > 100 mg/kg Dermal LD50 Rabbit LD50 Rabbit > 5000 mg/kg Inhalation LD50 Rato LD50 Rato > 218 mg/l	Inhalation		
LD50Rat34600 mg/kgChronic Inhalation PossInhalationNOELRatPage point 6 hoursPETROLEUM DISTILLATES, HYDE/TEATED HEAVY PARAFFINIC (CAS 64742-54-7)Permal Dermal LD50RabinSoon mg/kgInhalationPage point 6 hoursInhalationPage point 6 hours	LC50	Rat	12.4 mg/l, 4 hours
Chronic Inhalation Inhalation > 922 ppm, 6 hours NOEL Rat > 922 ppm, 6 hours PETROLEUM DISTILLATES, HYDROTREATED HEAVY PARAFFINIC (CAS 64742-54-7) - Acute - - Dermal - - LD50 Rabbit - - Inhalation - - - LC50 Rat 2.18 mg/l	Oral		
Inhalation NOEL Rat > 922 ppm, 6 hours PETROLEUM DISTILLATES, HYDREATED HEAVY PARAFFINIC (CAS 64742-54	LD50	Rat	34600 mg/kg
NOELRat> 922 ppm, 6 hoursPETROLEUM DISTILLATES, HYDROTREATED HEAVY PARAFFINIC (CAS 64742-54-7)AcuteDermalDermalEdbitLD50RabbitInhalationLC50Rat2.18 mg/l	Chronic		
PETROLEUM DISTILLATES, HYDROREATED HEAVY PARAFFINIC (CAS 64742-54-7 Acute Dermal LD50 Rabbit Rabbit LD50 Rabbit Rabbit LC50 Rat Rat Rabbit Rabbit Rat Rabbit Rabbi	Inhalation		
Acute Jermal 5000 mg/kg LD50 Rabbit > 5000 mg/kg Inhalation LC50 Rat 2.18 mg/l	NOEL	Rat	> 922 ppm, 6 hours
DermalLD50Rabbit> 5000 mg/kgInhalationLC50Rat2.18 mg/l	PETROLEUM DISTILLATE	S, HYDROTREATED HEAVY	2 PARAFFINIC (CAS 64742-54-7)
LD50 Rabbit > 5000 mg/kg Inhalation	Acute		
Inhalation LC50 Rat 2.18 mg/l	Dermal		
LC50 Rat 2.18 mg/l	LD50	Rabbit	> 5000 mg/kg
-	Inhalation		
Oral	LC50	Rat	2.18 mg/l
	Oral		
LD50 Rat > 5000 mg/kg	LD50	Rat	> 5000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation. Defatting, drying and cracking of skin.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization	1	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
US. OSHA Specifically Regunation Not listed.	ulated Substances (29 CFR 1910.1001-1050)	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Narcotic effects.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death.	
Chronic effects	Prolonged inhalation may be harmful.	

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results	
C9-C11 ISOALKANES (CAS	68551-16-6)		
Aquatic				
Acute				
Crustacea	EC50	Daphnia	1000 mg/l, 48 hours	
Fish	LC50	Rainbow Trout	1000 mg/l, 96 hours	
PETROLEUM DISTILLATES	, HYDROTR	EATED HEAVY PARAFFINIC (CAS	S 64742-54-7)	
Aquatic				
Acute				
Crustacea	EC50	Daphnia	> 1000 mg/l, 48 hours	
Fish	LC50	Oncorhynchus mykiss	> 5000 mg/l, 96 hours	
oaccumulative potential obility in soil her adverse effects	No data a No other	No data available. No data available. No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		
3. Disposal consideration	ons			
sposal instructions	chemical	Consult authorities before disposal. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.		
cal disposal regulations	Dispose i	Dispose in accordance with all applicable regulations.		
zardous waste code		The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		
aste from residues / unused oducts	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).			
ontaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.			

Contaminated packaging should be taken to an approved waste handling site for recycling or disposal. Empty containers Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

DOT

DOT	
UN number	UN1268
UN proper shipping name	PETROLEUM PRODUCTS, N.O.S. (C9-C11 ISOALKANES)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	144, B1, IB3, T4, TP1, TP29
Packaging exceptions	150
Packaging non bulk	203
Packaging bulk	242
	s material may be transported as "non regulated" by DOT if all criteria referenced in 49 CFR are
met and it is in "non-bulk"packa	ages (119 gallons or less).
ΙΑΤΑ	
UN number	UN1268
UN proper shipping name	Petroleum products, n.o.s. (C9-C11 ISOALKANES)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo	Allowed.
aircraft	
Cargo aircraft only	Allowed.
IMDG	
UN number	UN1268
UN proper shipping name	PETROLEUM PRODUCTS, N.O.S. (C9-C11 ISOALKANES)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not established.
Annex II of MARPOL 73/78 and	
the IBC Code	
DOT	





15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. It may be reportable under the provisions of SARA Sections 311 and 312 if specific threshold criteria are met or exceeded.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Hazard categories

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes chemical

nemicai

SARA 313 (TRI reporting) Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water ActNot regulated.(SDWA)Not regulated.Food and DrugNot regulated.

Administration (FDA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed.

US. Massachusetts RTK - Substance List

Not regulated.

- US. New Jersey Worker and Community Right-to-Know Act
 - Not listed.
- US. Pennsylvania Worker and Community Right-to-Know Law

Not listed.

US. Rhode Island RTK

Not regulated.

California South Coast Air Quality Management District (SCAQMD) Rule 1144 (VOC Emissions) This product is subject to SCAQMD Rule 1144; it is not compliant and shall not be sold and used in the SCAQMD. The VOC content of the product is 669 g/L, measured by ASTM Method E-1868-10. This product has a specified VOC limit of 50 g/L.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory or exempt (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Yes" indicates this product co	mplies with the inventory requirements administered by the governing countri	ry(s)

16. Other information, including date of preparation or last revision

Issue date	03-26-2015
Revision date	04-28-2015
Version #	02
Further information	Not available.
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision Information	Physical & Chemical Properties: Multiple Properties